

## Milliken Obex<sup>®</sup> Forma<sup>™</sup> 16mm



### Specification:

#### *Syncros 16mm Milliken Obex<sup>®</sup> Forma<sup>™</sup> in Closed / Open Format*

Tile Material:	UV Resistant PVC
Tile Construction:	Closed / Open
Total thickness:	16mm
Tile Size:	Nominal 200 x200mm, usable 195 xs195mm when installed
Yarn Composition:	100% Polyamide 6.6 - Mono & Multi filaments
Yarn Count:	5980Dtex
Construction:	Cut Pile
Tuft Method:	Straight Stitch
Pile Height:	6.75mm
Stitch Density:	5.5spi
Total fabric Weight:	1075g/m <sup>2</sup>
Total Weight:	9.11 kg per m <sup>2</sup> (Open) 10.4 kg per m <sup>2</sup> (Closed)
Washing (staining):	N/A (ISO 105-A04)
Washing (fading):	N/A (ISO 105-A04)
Light:	>6 (ISO 105-B01)
Composition:	100% PVC
Flammability;	low radius of effect of ignition (BS4790)



Friction resistance;	Class B – DS/EN ISO 8295(2004)
Wear resistance:	pass (66,000 cycles Vetterman test)



Open Format



Product: Milliken Obex<sup>®</sup> Forma<sup>™</sup> 16mm\* ? 11mm Closed / Open format entrance mat system in Ammonite \*, Twilight \*, Ash \*, Volcano \*, Bark \*, Fern \*, Sand\*, Lagoon\* to suit matwell size:.....  
Supplied and installed if required by Syncros Entrance Matting Systems, Triumph Way, Kempston, Beds, MK42 7QB, and Tel. 01234 314314 / Fax 01234 314306 / E-mail: [sales@syncros.co.uk](mailto:sales@syncros.co.uk) in accordance with the manufacturer's installation details.

## Milliken Obex<sup>®</sup> Forma<sup>™</sup> 11mm



### Specification:

#### Syncros 11mm Milliken Obex<sup>®</sup> Forma<sup>™</sup> in Closed Format

Tile Material:	UV Resistant PVC
Tile Construction:	Closed
Total thickness:	11mm
Tile Size:	Nominal 200 x200mm, 195 xs195mm when installed
Yarn Composition:	100% Polyamide 6.6 - Mono & Multi filaments
Yarn Count:	5980Dtex



11mm Closed Format

Tufting Specification;	
Construction:	Cut Pile
Tuft Method:	Straight Stitch
Pile Height:	6.75mm
Stitch Density:	5.5spi
Total fabric Weight:	1075g/m <sup>2</sup>

Yarn Colour Fastness;	
Washing (staining):	N/A (ISO 105-A04)
Washing (fading):	N/A (ISO 105-A04)
Light:	>6 (ISO 105-B01)

Tile Construction;	
Composition:	100% PVC
Mass:	6850g/m <sup>2</sup>
Tile thickness:	11mm

Performance:	
Flammability;	low radius of effect of ignition (BS4790)
Friction resistance;	B – DS/EN ISO 8295 (2004)
Wear resistance:	pass (22,000 cycles Vetterman test)



Lagoon Ammonite Twilight Sand Ash Volcano Fern Bark



Colours on computer-generated artwork do not accurately match actual mat colours.  
Please refer to colour swatch samples.