


3M Safety-Walk Wet Area Matting

3M Safety-Walk Wet Area Mating 1500




Description: Unbacked, open matting made from continuous coiled Vinyl filaments to provide an anti-slip, comfortable and attractive walking surface suitable for barefoot traffic.




Colours:

Horizon Blue held in stock

Hunter Green & Caravan Gold to order

Typical properties		Average values
		Thickness 9.0 mm
		Weight 2.0 kg/m ²
		Fire Retardancy NF P82507
		Microbiological properties ASTM G-21-90
		Inhibiting to fungal growth
		Chemical resistance Resist most cleaning and disinfecting chemicals

Flexible, comfortable and safe vinyl coils for shoes or barefoot application




Open, unbacked web construction to provide good water drainage and easy cleaning

side view

3M Safety-Walk Wet Area Mating 3200



Description: Unbacked, matting in a flexible vinyl with an open mesh that allows water to run through the matting so that the surface stays drier than the surrounding area.




Colours:

Horizon Blue held in stock

Wheat to order

Typical properties		Average values
		Thickness 6.0 mm
		Weight 3.9 kg/m ²
		Coefficient of friction ASTM D-1894
		>0.58
		DNV S1097 (ist NB)
		A+B+C
		Fire Retardancy ASTM E 648-95a
		>1.00 W/cm ²
		Microbiological properties ASTM G-21-90
		Inhibiting to fungal growth
		Chemical resistance Resist most cleaning and disinfecting chemicals

Light weight open construction to assure antislip properties and good water drainage in barefoot applications



Special fungus and mildew resistant vinyl material easy to clean – resist to most cleaning and disinfecting chemicals

top view