

Rawson Fibre Bonded Range



Eurocord 27 options
Sheet & Tile



Felkirk 25 options
Sheet & Tile



Castle 9 options
Tile only



Freeway 27 options
Sheet & Tile




Primary Colours
5 options
Sheet & Tile



Fresca 10 options
Sheet & Tile



Champion 12 options
Sheet & Tile



Denby 12 options
Sheet only



Eurocord

Technical Specifications

Fibre Type	80% Polypropylene 20% Polyester Perma Fresh®	
	Sheet	Tile
Fibre Weight (+/-10%)	900g/m ²	900g/m ²
Total Carpet Weight (+/-10%)	1150g/m ²	4150g/m ²
Total Thickness (+/-10%)	5.8mm	6.7mm
Dimensions	2x30m	50 x 50 cm
Backing Material		Bitumen
Tiles per Box		20

Industry Suitability

All public and private sector buildings, showrooms, corridors, halls, banks, offices and places of worship.

Performance/Durability

BS4939 Static	BS4502 Dynamic	BS1006 Light	BS1006 Shampoo	DD68 Voltage	Body	IBM ICL	Castor Chair	BS4790 Hot Nut
>80% Recovery	6+	4+	<2 KV	Pass	Pass	Pass	Pass	Low Radius



Felkirk

Technical Specifications

Fibre Type	80% Polypropylene 20% Polyester	
	Sheet	Tile
Fibre Weight (+/-10%)	1000g/m2	1000g/m2
Total Carpet Weight (+/-10%)	1300g/m2	4300g/m2
Total Thickness (+/-10%)	9.0mm	9.0mm
Dimensions	2x30m	50 x 50 cm
Backing Material	Bitumen	
Tiles per Box	16	

Industry Suitability

Schools, universities, residences, offices, retail outlets, commercial institutions and general public and private sector buildings.

Performance/Durability

BS4939 Static	BS4502 Dynamic	BS1006 Light	BS1006 Shampoo	DD68 Body Voltage	IBM ICL	Castor Chair	BS4790 Hot Nut
>80% Recovery	6+	4+	<2 KV	Pass	Pass	Low Radius	

Freeway

Technical Specifications

Fibre Type	80% Polypropylene 20% Polyester	
	Sheet	Tile
Fibre Weight (+/-10%)	900g/m2	900g/m2
Total Carpet Weight (+/-10%)	1100g/m2	4100g/m2
Total Thickness (+/-10%)	6.0mm	7.0mm
Dimensions	2x30m	50 x 50 cm
Backing Material	Bitumen	
Tiles per Box	20	

Industry Suitability

Classrooms, corridors, stairs, offices, retail shops, banks, places of worship, pubs, exhibitions, caravans, mobile homes, public and private sector buildings.

Performance/Durability

BS4939 Static	BS4502 Dynamic	BS1006 Light	BS1006 Shampoo	DD68 Body Voltage	IBM ICL	Castor Chair	BS4790 Hot Nut
>80% Recovery	6+	4+	<2 KV	Pass	Pass	Low Radius	



Fresca

Technical Specifications

Fibre Type	50% Polypropylene 50% Polyester	
	Sheet	Tile
Fibre Weight (+/-10%)	750g/m ²	750g/m ²
Total Carpet Weight (+/-10%)	1750g/m ²	3950g/m ²
Total Thickness (+/-10%)	6.5mm	8.0mm
Dimensions	2x30m	50 x 50 cm
Backing Material	Rubber	Bitumen
Tiles per Box	20	

Industry Suitability

All types of private and public sector offices, retails shops, banks, healthcare and sports and leisure centres.

Performance/Durability

BS4939 Static	BS4502 Dynamic	BS1006 Light	BS1006 Shampoo	DD68 Body Voltage	IBM ICL	Castor Chair	BS4790 Hot Nut
>80% Recovery		6+	4+	<2 KV	Pass	Pass	Low Radius

Champion

Technical Specifications

Fibre Type	80% Polypropylene 20% Polyester	
	Sheet	Tile
Fibre Weight (+/-10%)	900g/m ²	900g/m ²
Total Carpet Weight (+/-10%)	1100g/m ²	4100g/m ²
Total Thickness (+/-10%)	6.6mm	8.5mm
Dimensions	2x30m	50 x 50 cm
Backing Material	Bitumen	
Tiles per Box	20	

Industry Suitability

Public and private sector buildings, shops, offices, commercial institutions, retail, banks, health, sport and leisure centres.

Performance/Durability

BS4939 Static	BS4502 Dynamic	BS1006 Light	BS1006 Shampoo	DD68 Body Voltage	IBM ICL	Castor Chair	BS4790 Hot Nut
>80% Recovery		6+	4+	<2 KV	Pass	Pass	Low Radius



Denby

Technical Specifications

Fibre Type	80% Polypropylene 20% Polyester
Fibre Weight (+/-10%)	720g/m ²
Total Carpet Weight (+/-10%)	860g/m ²
Total Thickness (+/-10%)	5.0mm
Dimensions	2x30m

Industry Suitability

Public and private sector buildings, halls, schools, retail, commercial institutions and libraries etc.

Performance/Durability

BS4939 Static	BS4502 Dynamic	BS1006 Light	BS1006 Shampoo	DD68 Body Voltage	IBM ICL	Castor Chair	BS4790 Hot Nut
>80% Recovery	6+	4+	<2 KV	Pass	Pass	Low Radius	

